



Part Number: 10GB24C

Product Description

Category 6A (500MHz), 4-Pair, U/UTP, Premise Horizontal Cable, 23 AWG Solid Bare Copper Conductors, Polyethylene Insulation, LSZH Jacket

Technical Specifications

Product Overview

Environmental Space:	Indoor/Outdoor - Euroclass Cca
----------------------	--------------------------------

Physical Characteristics (Overall)

Conductor

AWG	Material	No. of Pairs
23	BC - Bare Copper	4

Conductor Count:	8
Conductor Size:	23 AWG

Insulation

Material	Nominal Diameter
Polyethylene	1.2 mm

Bonded-Pair:	No
--------------	----

Color Chart

Number	Color
Pair 1	White / Blue & Blue
Pair 2	White / Orange & Orange
Pair 3	White / Green & Green
Pair 4	White / Brown & Brown

Outer Shield Material

Material
Special barrier tape

Outer Jacket Material

Material	Nominal Diameter	Diameter +/- Tolerance
LSZH / FRNC	7.8 mm	0.3 mm

Construction and Dimensions

Min Elongation at Breakof Conductors:	10 %
Min Elongation at Breakof Insulation:	100 %

Cabling

Description	
4 pairs twisted together + cross web of polyolefin + overlapping polyester foil over cable core	
Min Elongation at Breakof Jacket:	100 %
Min Tensile Strength of Jacket:	9 MPa

Electrical Characteristics

Conductor DCR

Max. Conductor DCR	Max DCR Unbalanced Between Pairs [%]	Max. DCR Unbalanced Within Pair [%]
95 Ohm/km	4 %	2 %

Capacitance

Max. Capacitance Unbalanced Pair to Pair	Max. Mutual Capacitance
1,600 pF/m	56 pF/m

High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss	Nom. ACR [dB]
1 MHz	2.1 dB/100m	73.2 dB
4 MHz	3.8 dB/100m	62.5 dB
10 MHz	5.9 dB/100m	54.4 dB
16 MHz	7.5 dB/100m	
31.2 MHz	10.5 dB/100m	
62.5 MHz	15 dB/100m	
100 MHz	19.1 dB/100m	
125 MHz	21.5 dB/100m	
200 MHz	27.6 dB/100m	
250 MHz	31.1 dB/100m	
300 MHz	34.3 dB/100m	
500 MHz	45.3 dB/100m	

Delay

Max. Delay Skew	Nominal Velocity of Propagation (VP) [%]
45 ns/100m	67 %

High Freq

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Min. NEXT [dB]	Min. PSNEXT [dB]	Min. ACR [dB]	Min. PSACR [dB]	Min. ACRF (ELFEXT) [dB]	Min. PSACRF (PSELFEXT) [dB]	Min. RL (Return Loss) [dB]	Min. PSANEXT	Min. PSAACRF	Min. TCL [dB]	Min. ELTCTL [dB]
1 MHz	2.1 dB/100m	75.3 dB	72.3 dB	73.2 dB	67.0 dB	68 dB	65.0 dB	20 dB	67.0 dB	67 dB	40 dB	35 dB
4 MHz	3.8 dB/100m	66.3 dB	63.3 dB	62.5 dB	66.2 dB	56 dB	53.0 dB	23 dB	67.0 dB	66.2 dB	34 dB	23 dB
10 MHz	5.9 dB/100m	60.3 dB	57.3 dB	54.4 dB	58.2 dB	48 dB	45.0 dB	25 dB	67.0 dB	58.2 dB	30 dB	15 dB
16 MHz	7.5 dB/100m	57.2 dB	54.2 dB	49.8 dB	54.1 dB	43.9 dB	40.9 dB	25 dB	67.0 dB	54.1 dB	28 dB	10.9 dB
31.2 MHz	10.5 dB/100m	52.9 dB	49.9 dB	42.4 dB	48.3 dB	38.1 dB	35.1 dB	23.6 dB	67.0 dB	48.3 dB	25.1 dB	5.1 dB
62.5 MHz	15 dB/100m	48.4 dB	45.4 dB	33.4 dB	42.3 dB	32.1 dB	29.1 dB	21.5 dB	65.6 dB	42.3 dB	22 dB	
100 MHz	19.1 dB/100m	45.3 dB	42.3 dB	26.2 dB	38.2 dB	28 dB	25.0 dB	20.1 dB	62.5 dB	38.2 dB	20 dB	
125 MHz	21.5 dB/100m	43.8 dB	40.8 dB	22.3 dB	36.3 dB	26.1 dB	23.1 dB	19.4 dB	61.0 dB	36.3 dB	19 dB	
200 MHz	27.6 dB/100m	40.8 dB	37.8 dB	13.2 dB	32.2 dB	22 dB	19.0 dB	18 dB	58.0 dB	32.2 dB	17 dB	
250 MHz	31.1 dB/100m	39.3 dB	36.3 dB	8.3 dB	30.2 dB	20 dB	17.0 dB	17.3 dB	56.5 dB	30.2 dB	16 dB	
300 MHz	34.3 dB/100m	38.1 dB	35.1 dB	3.9 dB	28.7 dB	18.5 dB	15.5 dB	17.3 dB	55.3 dB	28.7 dB		
500 MHz	45.3 dB/100m	34.8 dB	31.8 dB	-10.4 dB	24.2 dB	14 dB	11.0 dB	17.3 dB	52.0 dB	24.2 dB		

Current

Max. Recommended Current [A]
1.5 A

Temperature Range

Installation Temp Range:	0°C To +50°C
Operating Temp Range:	-30°C To 60°C

Mechanical Characteristics

Bulk Cable Weight:	50 kg/km
Max Recommended Pulling Tension:	110 N

Standards

ISO/IEC Compliance:	ISO/IEC 11801 Ed. 2.2:2002/A2:2010/C1:2011
CPR Euroclass:	Cca-s1,d1,a1
CENELEC Compliance:	EN 50173-1 Ed. 3:2011

Data Category:	Category 6A
ANSI Compliance:	ANSI/TIA/EIA 568-C.2 (2009)

Applicable Environmental and Other Programs

EU RoHS Compliance Date (yyyy-mm-dd):	2015-08-24
---------------------------------------	------------

Flammability, LSOH, Toxicity Testing

ISO/IEC Flammability:	IEC 60332-1
Burning Load:	550 kJ/m
Amount of Halogen acc. to IEC 60754-1 & EN50267-1:	Zero

Part Number

Variants

Item #	Color
10GB24C.06500	Blue

Patent:	https://www.belden.com/resources/patents
---------	---

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.